

Amendments to and Listing of the Claims:

Please amend claim 1 so that the claims read as follows:

1. (currently amended) A material for a thermal fuse element wherein said material has an alloy composition in which Bi is larger than 50% and 56% or smaller, and a balance is Sn, and wherein the thermal fuse element is divided by surface tension.
2. (withdrawn) A material for a thermal fuse element wherein 0.1 to 7.0 weight parts of one, or two or more elements selected from the group consisting of Ag, Au, Cu, Ni, Pd, Pt, Ga, and Ge are added to 100 weight parts of an alloy composition of claim 1.
3. (original) An alloy type thermal fuse wherein a material for a thermal fuse element of claim 1 is used as a fuse element.
4. (withdrawn) An alloy type thermal fuse wherein a material for a thermal fuse element of claim 2 is used as a fuse element.
5. (original) An alloy type thermal fuse according to claim 3, wherein said fuse element contains inevitable impurities.
6. (withdrawn) An alloy type thermal fuse according to claim 4, wherein said fuse element contains inevitable impurities.
7. (original) An alloy type thermal fuse according to claim 3, wherein said fuse element is connected between lead conductors, and at least a portion of each of said lead conductors which is bonded to said fuse element is covered with a Sn or Ag film.
8. (withdrawn) An alloy type thermal fuse according to claim 4, wherein said fuse element is connected between lead conductors, and at least a portion of each of said lead conductors which is bonded to said fuse element is covered with a Sn or Ag film.
9. (original) An alloy type thermal fuse according to claim 5, wherein said fuse element is connected between lead conductors, and at least a portion of each of said lead conductors which is bonded to said fuse element is covered with a Sn or Ag film.

10. (withdrawn) An alloy type thermal fuse according to claim 6, wherein said fuse element is connected between lead conductors, and at least a portion of each of said lead conductors which is bonded to said fuse element is covered with a Sn or Ag film.

11. (original) An alloy type thermal fuse according to claim 3, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

12. (withdrawn) An alloy type thermal fuse according to claim 4, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

13. (original) An alloy type thermal fuse according to claim 5, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

14. (withdrawn) An alloy type thermal fuse according to claim 6, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

15. (original) An alloy type thermal fuse according to claim 7, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse

element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

16. (withdrawn) An alloy type thermal fuse according to claim 8, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

17. (original) An alloy type thermal fuse according to claim 9, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

18. (withdrawn) An alloy type thermal fuse according to claim 10, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

19. (original) An alloy type thermal fuse according to claim 3, wherein a pair of film electrodes are formed on a substrate by printing conductive paste containing metal particles and a binder, said fuse element is connected between said film electrodes, and said metal particles are made of a material selected from the group consisting of Ag, Ag-Pd, Ag-Pt, Au, Ni, and Cu.

20. (withdrawn) An alloy type thermal fuse according to claim 4, wherein a pair of film electrodes are formed on a substrate by printing conductive paste containing metal particles and a binder, said fuse element is connected between said film electrodes, and said metal

particles are made of a material selected from the group consisting of Ag, Ag-Pd, Ag-Pt, Au, Ni, and Cu.

21. (original) An alloy type thermal fuse according to claim 5, wherein a pair of film electrodes are formed on a substrate by printing conductive paste containing metal particles and a binder, said fuse element is connected between said film electrodes, and said metal particles are made of a material selected from the group consisting of Ag, Ag-Pd, Ag-Pt, Au, Ni, and Cu.

22. (withdrawn) An alloy type thermal fuse according to claim 6, wherein a pair of film electrodes are formed on a substrate by printing conductive paste containing metal particles and a binder, said fuse element is connected between said film electrodes, and said metal particles are made of a material selected from the group consisting of Ag, Ag-Pd, Ag-Pt, Au, Ni, and Cu.

23. (original) An alloy type thermal fuse according to claim 3, wherein a heating element for fusing off said fuse element is additionally disposed.

24. (withdrawn) An alloy type thermal fuse according to claim 4, wherein a heating element for fusing off said fuse element is additionally disposed.

25. (original) An alloy type thermal fuse according to claim 5, wherein a heating element for fusing off said fuse element is additionally disposed.

26. (withdrawn) An alloy type thermal fuse according to claim 6, wherein a heating element for fusing off said fuse element is additionally disposed.

27. (original) An alloy type thermal fuse according to claim 7, wherein a heating element for fusing off said fuse element is additionally disposed.

28. (withdrawn) An alloy type thermal fuse according to claim 8, wherein a heating element for fusing off said fuse element is additionally disposed.

29. (original) An alloy type thermal fuse according to claim 9, wherein a heating element for fusing off said fuse element is additionally disposed.

30. (withdrawn) An alloy type thermal fuse according to claim 10, wherein a heating element for fusing off said fuse element is additionally disposed.

31. (original) An alloy type thermal fuse according to claim 11, wherein a heating element for fusing off said fuse element is additionally disposed.

32. (withdrawn) An alloy type thermal fuse according to claim 12, wherein a heating element for fusing off said fuse element is additionally disposed.

33. (original) An alloy type thermal fuse according to claim 13, wherein a heating element for fusing off said fuse element is additionally disposed.

34. (withdrawn) An alloy type thermal fuse according to claim 14, wherein a heating element for fusing off said fuse element is additionally disposed.

35. (original) An alloy type thermal fuse according to claim 15, wherein a heating element for fusing off said fuse element is additionally disposed.

36. (withdrawn) An alloy type thermal fuse according to claim 16, wherein a heating element for fusing off said fuse element is additionally disposed.

37. (original) An alloy type thermal fuse according to claim 17, wherein a heating element for fusing off said fuse element is additionally disposed.

38. (withdrawn) An alloy type thermal fuse according to claim 18, wherein a heating element for fusing off said fuse element is additionally disposed.

39. (original) An alloy type thermal fuse according to claim 19, wherein a heating element for fusing off said fuse element is additionally disposed.

40. (withdrawn) An alloy type thermal fuse according to claim 20, wherein a heating element for fusing off said fuse element is additionally disposed.

41. (original) An alloy type thermal fuse according to claim 21, wherein a heating element for fusing off said fuse element is additionally disposed.

42. (withdrawn) An alloy type thermal fuse according to claim 22, wherein a heating element for fusing off said fuse element is additionally disposed.